



14.2 Calcium Bromide

SINGLE SALT BLEND

Overview

14.2 pound per gallon calcium bromide solution is used as a completion, workover, or packer fluid. It can be used as a single salt fluid or as a component in a multi-salt blend. It can also be used as a spike fluid to increase density.

Features and Benefits

- Inhibitive properties can prevent hydration that may lead to migration of swelling clays.
- Can be blended with other clear brine fluids to achieve a specific density and crystallization temperature.
- Generally compatible with most oilfield elastomers.

Caution: Fluid additives, formation water and other contacting fluids should be screened for compatibility with the brine prior to use.

Physical Properties

Appearance	Colorless to straw colored liquid
pH	6.0 - 8.0
Specific gravity	1.70 @ 70°F (21°C)
Crystallization Temperature	10°F

Packaging Information

Bulk Liquid

Recommended Treatment

Use the amount necessary for density adjustment. See blending tables or consult a TETRA representative for specific requirements.

Safety and Handling

Avoid skin and eye contact, inhalation or ingestion. For skin contact, wash with soap and large quantities of water. For eye contact, flush with large quantities of water. Use properly designed respirator if adequate ventilation is not available. Refer to the Safety Data Sheet for specific details.

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.