



Clear Brine Fluids Facility — Pecos, Texas

538 West CR 404, Pecos, TX 79772
 Phone: +1 432.366.0630

GENERAL DESCRIPTION

The TETRA clear brine fluids (CBF) facility in Pecos, TX, is strategically located to serve oil and gas operations in the heart of the Permian — 24 hours a day, seven days a week, 365 days a year.

With two stationary 250 bbl blending tanks, the facility provides a comprehensive range of clear brine fluids, heavy brines, and chemical blends for any of your well needs. For drill-out operations, this facility has a fleet of portable mixing plants available for quick deployment. Facility services also include on-site fluid technicians as well as sourcing of third-party trucking for fluid transport.

KEY FACTS

+

11,000 bbl
CBF Storage Capacity

+

2,100 sq ft
Warehouse Space

+

ZERO
Environmental Incidents Since Inception (3+ yrs)

+

24/7
On-site Qualified & Experienced Fluid Techs

PRODUCTS & SERVICES

- » Full line of CBFs: Calcium Bromide, Calcium Chloride, Potassium Chloride, Sodium Chloride, Zinc Bromide and custom density blends
- » CBF additives including biocides, corrosion inhibitors, friction reducers, hydrogen sulfide scavengers, oxygen scavengers, and more, creating packer fluids of any density — limitless combinations to fulfill specialized needs
- » Expert fluid technicians, available 24/7
- » Sourcing of third-party fluid trucking for chemical transport
- » Stock of PPE for purchase, including chemical suits, safety packs, and steel-toe rubber boots

CAPACITIES

- » 2 stationary 250 bbl blending tanks
- » 3 portable mixing plants for mobile blending
- » 11,000 bbl CBF storage capacity
- » 2,100 sq ft of warehouse space



Clear Brine Fluids Facility — Pecos, Texas

538 West CR 404, Pecos, TX 79772
 Phone: +1 432.366.0630

Clear Brine Fluids	8.5 lb/gal–19.2 lb/gal
Fresh Water (H ₂ O)	8.4 lb/gal
Potassium Chloride (KCl)	8.4-9.7 lb/gal
Sodium Chloride (NaCl ₂)	8.4-10 lb/gal
Calcium Chloride (CaCl ₂)	10.1-11.6 lb/gal
Calcium Bromide (CaBr ₂)	11.7-15.1 lb/gal
Zinc Bromide (ZnBr ₂)	15.2-19.2 lb/gal

