



TETRABreak HA

ACID PRECURSOR

Overview

TETRABreak HA is liquid organic acid precursor designed to degrade polymers and starches used in drill-in fluids.

Features and Benefits

- External breaker of filter cakes deposited by brine base drill-in fluids.
- Effective at temperature ranging from 70°F to 300°F.
- Compatible and can be used in fresh water, sea water and clear brine fluids
- Enhanced degradation of polymers and starches in the filtercake when combined with TETRAzyme S1
- Low environmental impact and high biodegradability

Applicable Information

TETRABreak HA acid precursor is easily mixed in fresh water, sea water and clear brine fluids. The pH of the carrier fluid should be in the range of 6 - 8 prior to mixing with TETRABreak HA acid precursor.

Physical Properties

Appearance	Clear liquid
Specific gravity	1.18 @ 70°F
Acidity	0.3% maximum
Water Solubility	Soluble

Packaging Information

TETRABreak HA is supplied in 240 Kg steel drums
TETRABreak HA is supplied in 1,000 Kg IBC tanks

Recommended Treatment

The recommended concentration of TETRABreak HA acid precursor is in the range of 5% to 10% wt./vol. in the carrier fluid. The treatment concentration of TETRABreak HA is dependent upon the bottom hole temperature and time interval for degradation. Consult a TETRA representative to discuss specific applications.

Safety and Handling

Avoid skin and eye contact, inhalation or ingestion. For skin contact, wash with soap and large quantities of water. For eye contact, flush with large quantities of water. Use properly designed respirator if adequate ventilation is not available. Refer to the Safety Data Sheet for specific details.

Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. Further, nothing contained herein shall be taken as a recommendation to manufacture or use any of the herein described materials or processes in violation of existing or future patents.